

Preliminary Measurements in Search for 0.1 meV Axions and Hidden Photons using Copper Resonant Cavities




P. L. SLOCUM, O. K. BAKER, J. L. HIRSHFIELD,
Y. JIANG, G. KAZAKEVITCH,
S. KAZAKOV, M. A. LAPOINTE, A. MARTIN,
S. SHCHELKUNOV, A. SZYMKOWIAK

YALE UNIVERSITY

Overview of experiment



- LNB ($g=10^{-6}/\text{GeV}$) and HSP ($\chi=10^{-7}$) near 0.1 meV
- Generation – regeneration experiment with 2 Cu resonant cavities inside 7 Tesla magnet.
- MW 34 GHz magnicon at Yale.




Drawing courtesy of Will Emmet


Cryostat and magnet




- 7 Tesla cryomagnet, 89 mm warm bore.
- Liquid He flow cryostat extending into magnet bore. Sample region in cold He vapor, at center of magnetic field.




Cryostat temperatures



Receiver



Receiver layout



Receiver status





- Room temperature components were assembled and powered two weeks ago.
 - 4 GHz amplifier chain had been oscillating due to loose ground lug. Qualitative performance now looks good. More tests pending.
 - 590 MHz amplifiers are working and have noise power less than 10^{-11} Watts per MHz between 560 and 620 MHz.
 - Oscillators working well.
- Cryogenic HEMT amplifier has been cooled to 77 K and tested.
 - DC specs match those of supplier at 300 K and 20 K.
 - Broadband noise power at 77 K was undetectable with Schottky diode (sensitivity $0.5 \text{ mV}/\mu\text{W}$).


Signal Cavity



- TE₀₁₁ mode.
- $Q \sim 1.5 \times 10^4$
- Cooled to < 10 K.




Braze oven




Drive Cavity



- TE₀₁₁ mode.
- $Q \sim 5000$
- Dissipates 10 W average power
- Water cooled.
- 4 pressure points for initial tuning.




Magnicon intrapulse phase deviations



Signal cavity – sweep range for halo axions



- Tuning plunger can move +/- 2 mm.
- For cylindrical cavity TE₀₁₁ mode:
 - +2 mm --> 33.5 GHz = 0.137 meV
 - -2 mm --> 35 GHz = 0.143 meV.
- $g = 10^{-7}/\text{GeV}$ assuming $S/N \sim 1$. Integration time determines additional sensitivity.



C. G. Montgomery, Technique of Microwave Measurements, New York and London McGraw-Hill Book Company, Inc., p. 298, 1947.

Summary




- Equipment testing is going well:
 - Cryostat is cold. Tests are continuing.
 - Cryogenic amplifier has been cooled and tested outside the cryostat.
 - Room temperature receiver chain is assembled and powered. Specs look good.
 - Noise power of receiver parts has been hard to measure – a good problem.
- Next steps:
 - Finish machining and brazing cavities, get signal out of cryostat.
 - Drill hole in shielded room for waveguide.
 - Set up trigger and take data.

Auxiliary slides



34 GHz microwave source



- Output: 10 MW, 1 μ s pulses at 10 Hz. Bandwidth=1 MHz.
- 500 kV, 215 A e- beam transverse deflection system:
 - Drive cavity (11.4 GHz), 3 gain cavities, and two final cavities.
 - Transverse beam momentum is transferred to RF fields at high efficiency.

O. A. Nezhevenko et al., IEEE Transactions on Plasma Science, 0093-3813/04, 2004.

Photos courtesy of M. Lapointe

Expected Signal Power

For $g=2.5e-6/\text{GeV}$

$$\Pi_{\gamma \rightarrow \phi} \approx \frac{1}{4}(gBL)^2,$$

or $\Pi=10^{-15}$ for $B=8 \text{ T}$ and $L=10 \text{ cm}$.

Probability Π^2 yields the expected signal power:

$$P_{LNB} = P_{beam} \Pi^2 Q_1 Q_2.$$

T(K)	Q_1	Q_2	P_{LNB}	N_{phot} at 34 GHz
300	1.5e4	2.e3	10^{-21} W	66 phot/s
40	9.e4	1.2e4	10^{-20} W	660 phot/s

Expected Noise Power

$$\text{Friis' formula: } T_N = T_1 + \frac{T_2}{G_1} + \frac{T_3 - 1}{G_1 G_2} \dots$$

$$\Rightarrow T_N \approx 3(300\text{K}) + \frac{300\text{K}}{1000.} + \frac{300\text{K}}{1000.*10000.} + \dots \approx 900\text{K}.$$

Assuming a flat thermal noise spectrum,

$$P_N = k_B T_N B = (1.38\text{e-}23 \text{ J/K})(900 \text{ K})(10^6 \text{ Hz}) = 10^{-14} \text{ W}$$

With gating ($\times 10^{-5}$), $P_N \sim 10^{-19} \text{ W}$, or **5300 photons/s** at 34 GHz.

$$\text{From } \frac{N_s t}{\sqrt{N_B t}} \equiv 5 \text{ where } N_s = 66 \text{ Hz and } N_B = 5300 \text{ Hz,}$$

$$\Rightarrow t = 30 \text{ s at } T = 300\text{K} \text{ (or } 0.3 \text{ s at } T = 40\text{K}).$$